

Serial No. 09/727,313
Attorney Docket No. 020533.0345 (2001P21474US)

Amendments To the Claims:

Please amend the claims as shown. Applicants reserve the right to pursue any cancelled claims at a later date.

1.-30. (Canceled)

31. (Currently Amended) A method of communicating information, comprising:

at a first client, forming a first signal encapsulated point-to-point protocol data unit by encapsulating a point-to-point signal within appending a network address request header ~~to a point-to-point protocol data unit~~, wherein the point-to-point signal ~~protocol data unit~~ comprises a header including an identifier associated with a second client and a payload comprising information to be communicated to the second client;

at a tunneling server, receiving the first signal ~~encapsulated point-to-point protocol data unit~~, removing the network address request header, and encapsulating ~~appending to the header of the point-to-point signal within protocol data unit~~ a network address response header to form a second signal ~~encapsulated point-to-point protocol data unit~~; and

communicating the second signal toward ~~encapsulated point-to-point protocol data unit for receipt by~~ the second client.

32. (Original) The method of Claim 31, wherein the network address request header comprises a Dynamic Host Configuration Protocol DISCOVER header or a Bootstrap Protocol REQUEST header.

33. (Original) The method of Claim 31, wherein the network address response header comprises a Dynamic Host Configuration Protocol OFFER header or a Bootstrap Protocol RESPONSE header.

34. (Currently Amended) The method of Claim 31, wherein ~~the header of the point-to-point~~ signal is encapsulated within protocol data unit ~~comprises a tunneling header prior to being encapsulated into the network address request header appended to the~~

Serial No. 09/727,313
Attorney Docket No. 020533.0345 (2001P21474US)

~~point-to-point-protocol-data-unit~~, the tunneling header operable to facilitate maintenance of a tunneling session between the tunneling server and the first client.

35. (Original) The method of Claim 34, wherein the tunneling header comprises a tunneling header selected from the group consisting of a Layer Two Tunneling Protocol (L2TP) header, a Point to Point Tunneling Protocol (PPTP), or a Layer Two Forwarding (L2F) header.

36. (Currently Amended) A method of communicating in an enterprise network, comprising:

at a tunneling server, receiving from a first client a first signal, the first signal formed by encapsulating a an-encapsulated point-to-point signal within a network address request header, the point-to-point signal protocol-data-unit comprising a first header that includes an identifier associated with a second client, and a payload comprising information to be communicated to the second client, ~~and a network address request header appended to the first header;~~

encapsulating the first signal within appending a network address response header to the point-to-point-protocol-data-unit to form a second signal; and

communicating the second signal point-to-point-protocol-data-unit with the appended network address response header toward the second client.

37. (Original) The method of Claim 36, wherein the network address request header comprises a Dynamic Host Configuration Protocol DISCOVER header or a Bootstrap Protocol REQUEST header.

38. (Original) The method of Claim 36, wherein the network address response header comprises a Dynamic Host Configuration Protocol OFFER header or a Bootstrap Protocol RESPONSE header.

39. (Currently Amended) The method of Claim 36, wherein ~~the first header comprises a tunneling header appended to the point-to-point~~ signal is encapsulated within a

Serial No. 09/727,313
Attorney Docket No. 020533.0345 (2001P21474US)

tunneling header protocol data unit, the tunneling header operable to facilitate maintenance of a tunneling session between the tunneling server and the first client.

40. (Original) The method of Claim 39, wherein the tunneling header comprises a tunneling header selected from the group consisting of a Layer Two Tunneling Protocol (L2TP) header, a Point to Point Tunneling Protocol (PPTP), or a Layer Two Forwarding (L2F) header.

41. (Currently Amended) The method of Claim 36, wherein ~~the first header comprises a tunneling header appended to the point-to-point~~ signal is encapsulated within a tunneling header protocol data unit, the tunneling header operable to facilitate maintenance of a tunneling session between the tunneling server and the second client.

42. (Currently Amended) The method of Claim 36, wherein communicating the ~~second signal point-to-point protocol data unit with the appended network address response header~~ toward the second client comprises communicating the second signal point-to-point protocol data unit with the appended network address response header toward a router operable to relay the second signal point-to-point protocol data unit with the appended network address response header toward the second client without referencing a routing table indexed by data channel addresses.

43. (Original) The method of Claim 42, wherein the identifier comprises a control channel address identifying the second client, the control channel address being different than any data channel address recognized by the router.

44. (Original) The method of Claim 36, wherein the identifier comprises an identifier of the second client other than a control channel address, and further comprising accessing a memory to determine, based on the identifier, a control channel address of the second client.

Serial No. 09/727,313
Attorney Docket No. 020533.0345 (2001P21474US)

45. (Currently Amended) The method of Claim 36, wherein the point-to-point ~~signal protocol data unit~~ comprises information to be applied to an application residing at the second client.

46. (Original) The method of Claim 45, wherein the application residing at the second client comprises a maintenance application operable to diagnose operational characteristics of the second client.

47. (Currently Amended) The method of Claim 36, wherein the point-to-point ~~signal protocol data unit~~ comprises at least a portion of an application to be installed on the second client.

48. (Currently Amended) The method of Claim 36, further comprising removing the network address request header ~~appended to the first header~~ before encapsulating the first signal within appending the network address response header ~~to the point-to-point protocol data unit, the network address response header appended to the first header of the point-to-point protocol data unit.~~

49. (Currently Amended) A computer readable medium operable to execute the following steps on a processor of a computer:

at a tunneling server, receiving from a first client a first signal formed by encapsulating a point-to-point signal within a network address request header, the an-encapsulated point-to-point protocol data unit signal comprising a first header that includes an identifier associated with a second client, and a payload comprising information to be communicated to the second client, ~~and a network address request header appended to the first header;~~

removing the point-to-point signal from the first signal;

encapsulating the point-to-point signal within appending a network address response header to form a second signal to the point-to-point protocol data unit; and

communicating the second signal point-to-point protocol data unit with the appended network address response header toward the second client.

Serial No. 09/727,313
Attorney Docket No. 020533.0345 (2001P21474US)

50. (Currently Amended) The computer readable medium of Claim 49, wherein ~~the first header comprises a tunneling header appended to the point-to-point protocol data unit signal is encapsulated within a tunneling header~~, the tunneling header operable to facilitate maintenance of a tunneling session between the tunneling server and the first client.

51. (Currently Amended) The computer readable medium of Claim 49, wherein ~~the first header comprises a tunneling header appended to the point-to-point protocol data unit signal is encapsulated within a tunneling header~~, the tunneling header operable to facilitate maintenance of a tunneling session between the tunneling server and the second client.

52. (Currently Amended) The computer readable medium of Claim 49, wherein communicating the ~~point-to-point signal with the network address response header second signal~~ toward the second client comprises communicating the ~~point-to-point signal with the network address response header second signal~~ toward a router operable to relay the ~~point-to-point signal with the network address response header second signal~~ to the second client without referencing a routing table indexed by data channel addresses.

53. (Currently Amended) The computer readable medium of Claim 52, wherein the point-to-point ~~protocol data unit signal~~ comprises a control channel address identifying the second client, the control channel address being different than any data channel address recognized by the router.

54. (Original) The computer readable medium of Claim 49, wherein the first identifier comprises an identifier other than a control channel address of the second client, and further comprising accessing a memory to determine, based on the identifier, a control channel address of the second client.

55. (Currently Amended) The computer readable medium of Claim 49, wherein the point-to-point protocol ~~data unit~~ signal comprises information to be applied to an application residing at the destination client.

Serial No. 09/727,313
Attorney Docket No. 020533.0345 (2001P21474US)

56. (Currently Amended) The computer readable medium of Claim 49, wherein the point-to-point protocol ~~data-unit-signal~~ comprises at least a portion of an application to be installed on the second client.

57. (Canceled)

58. (Currently Amended) In an enterprise network comprising at least one client coupled to a tunneling server, a tunneling server comprising:

a tunneling module operable to receive a first signal formed by encapsulating a point-to-point signal protocol data-unit encapsulated within a network address request header; and

a protocol stack operable to process at least a portion of the ~~first point-to-point signal protocol data-unit~~ to identify a control channel address associated with a destination client;

wherein the tunneling module is further operable to encapsulate the first point-to-point ~~protocol data-unit signal~~ within a network address response header to form a second signal and wherein the tunneling server is operable to communicate the second signal encapsulated point-to-point data-unit toward the destination client.

59. (Original) The tunneling server of Claim 58, wherein the network address request header comprises a Dynamic Host Configuration Protocol DISCOVER header or a Bootstrap Protocol REQUEST header.

60. (Original) The tunneling server of Claim 58, wherein the network address response header comprises a Dynamic Host Configuration Protocol OFFER header or a Bootstrap Protocol response header.

61. (Currently Amended) The tunneling server of Claim 58, wherein the ~~first point-to-point signal protocol data-unit~~ comprises a control channel address identifying the destination client, and wherein the tunneling server is further operable to communicate the first signal encapsulated point-to-point protocol data-unit toward a router for forwarding to the destination client without reference to a routing table indexed by data channel addresses.

Serial No. 09/727,313
Attorney Docket No. 020533.0345 (2001P21474US)

62. (Currently Amended) The tunneling server of Claim 58, wherein the ~~first point-to-point protocol~~ signal is encapsulated within a tunneling header and further encapsulated within the network address request header, and wherein the tunneling module is operable to process the tunneling header to maintain a tunneling session between the tunneling server and a client originating the first signal point-to-point protocol data unit.

63. (Original) The tunneling server of Claim 62, wherein the tunneling header comprises a tunneling header selected from the group consisting of a Layer Two Tunneling Protocol (L2TP) header, a Point to Point Tunneling Protocol (PPTP), or a Layer Two Forwarding (L2F) header.

64. (Currently Amended) The tunneling server of Claim 58, wherein the tunneling module is operable to encapsulate the ~~first point-to-point signal protocol data unit~~ within a tunneling header before encapsulating the first point-to-point protocol data unit within the network address response header, the tunneling header operable to facilitate maintenance of a tunneling session between the tunneling server and the destination client.

65. (Currently Amended) The tunneling server of Claim 58, wherein the point-to-point signal protocol data unit comprises a payload comprising information to be applied to an application residing at the destination client.

66. (Original) The tunneling server of Claim 65, wherein the payload comprises information to be applied to a maintenance application residing at the destination client and operable to diagnose operational characteristics of the destination client.

67. (Currently Amended) A system operable to facilitate communication with a destination client in an enterprise network, the system comprising:

a first client comprising:

a protocol stack operable to generate a ~~first point-to-point~~ signal protocol data unit; and

Serial No. 09/727,313
Attorney Docket No. 020533.0345 (2001P21474US)

a tunneling module operable to encapsulate the ~~first~~ point-to-point signal data unit within a network address request header to form a first ~~encapsulated~~ signal;

wherein the first client is operable to communicate the first ~~encapsulated~~ signal toward a tunneling server; and

a tunneling server comprising:

a tunneling module operable to receive the first ~~encapsulated~~ signal; and

a protocol stack operable to process at least a portion of the ~~first~~ point-to-point ~~protocol~~ signal to identify a control channel address associated with a destination client;

wherein the tunneling module is further operable to encapsulate the ~~first~~ point-to-point ~~protocol~~ signal within a network address response header to form a second ~~encapsulated~~ signal and wherein the tunneling server is operable to communicate the second ~~encapsulated~~ signal toward the destination client.